

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 1056 (2004): Commercial Weights [PGD 26: Weights and Measures]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



भारतीय मानक
व्यावसायिक बाट — विशिष्टि
(तीसरा पुनरीक्षण)

Indian Standard
COMMERCIAL WEIGHTS — SPECIFICATION
(*Third Revision*)

ICS 01.060

© BIS 2004

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

FOREWORD

This Indian Standard (Third Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Weights and Measures Sectional Committee had been approved by the Basic and Production Engineering Division Council.

This standard was first published in 1957 on the recommendations of the Standing Metric Committee set up by the Government of India to formulate and implement the programme of changeover to metric system which was subsequently revised in 1965 and 1993. This revision has been taken up to update and bring it in line with the latest development taken place in this field. The following are the main modifications in this revision.

The parallelopiped weight of type 1 and type 2 have been deleted since these weights are suitable for verification of weighing machines and not as commercial weights.

The permissible errors have been aligned in line with as prescribed under the latest *Standards of Weights & Measures (General) Rules, 1987*.

The basic series of weights adopted in this standard is 5, 2, 2, 1 and therefore, for making complete sets, one additional weight of relevant decimal multiple of two will be necessary in addition to denominations of different series prescribed under 3. Indenters should bear this in mind when placing orders.

This standard prescribes hexagonal shape for cast iron and forged mild steel weights. In the case of brass or bronze weights, two shapes have been prescribed as follows:

- a) Cylindrical, with a knob on top for the general bullion trade; and
- b) Flat cylindrical, with straight side, for goldsmiths.

This standard does not prescribe the classes of trade for which different types of weights may be used. The following information may, however, serve as illustrations:

- a) *General trader's weights* — These are made of cast iron or forged mild steel. They are generally used for weighing materials, such as grains, salt, flour, pulses, seeds, spices, nuts, fruits, jaggery, ghee, butter, vegetables, oils, including edible oils and hydrogenated oil, sweet-meat, fish, fuel non-precious metals, etc.
- b) *Bullion and precision metal weights* — These are made in the solid form from brass or bronze and in the sheet form from stainless steel, aluminium, brass or nickel-silver. These are generally used for weighing bullion and precious metals.
- c) *Apothecary's and chemist's weights* — These are solid weights made of brass or bronze and sheet metal weights made of stainless steel, aluminium, brass or nickel-silver, and are used by apothecaries, and in similar trades.

The dimensions for weights of different types and denominations have been calculated by assuming a specific gravity of 7.15 g/cm³ for cast iron and 8.40 g/cm³ for brass and bronze. Further, it has been assumed that the weights have been adjusted by filling in one third of the loading hole with lead having specific gravity of 11.38 g/cm³.

In the preparation of this standard, considerable assistance has been derived from *Standards of Weights & Measures (General) Rules, 1987*.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

COMMERCIAL WEIGHTS — SPECIFICATION
(Third Revision)

1 SCOPE

1.1 This standard prescribes the requirements of the following categories of solid and sheet metal weights intended for use in normal commercial transactions:

- a) Iron weights, hexagonal (50 kg to 50 g);
- b) Brass and bronze weights (10 kg to 1 g); and
- c) Sheet metal weights (500 mg to 1 mg).

1.2 It does not cover proportional weights that are used, for instance, in certain types of weighing machines, weigh-bridges, etc.

2 REFERENCES

The following standards contain provisions which through reference in this text, constitute provision of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below:

<i>IS No.</i>	<i>Title</i>
210 : 1993	Grey iron castings — Specification (<i>fourth revision</i>)
292 : 1983	Leaded brass ingots and castings (<i>second revision</i>)
306 : 1983	Tin bronze ingots and castings (<i>third revision</i>)
319 : 1989	Free-cutting leaded brass bars, rods and sections (<i>fourth revision</i>)
410 : 1977	Cold rolled brass sheet, strip and foil (<i>third revision</i>)
737 : 1986	Wrought aluminium and aluminium alloy sheet and strip for general engineering purposes (<i>third revision</i>)
1570 (Part 5) : 1985	Schedules for wrought steels : Part 5 Stainless and heat resisting steels (<i>second revision</i>)

IS No.

Title

1977 : 1996 Low tensile structural steel — Specification (*third revision*)

3 DENOMINATIONS OF WEIGHTS

3.1 The denominations of the different types of weights shall be as follows.

3.1.1 Solid Metal Weights

Kilogram (kg) Series

Iron and Steel Weights	Brass and Bronze Weights
50	10
20	5
10	2
5	1
2	
1	

Gram (g) Series

Iron and Steel Weights	Brass and Bronze Weights
500	500
200	200
100	100
50	50
	20
	10
	5
	2
	1

3.1.2 Sheet Metal Weights

3.1.2.1 Milligram (mg) series

500, 200, 100, 50, 20, 10, 5, 2 and 1.

3.1.3 The actual series to be used in practice shall consist of two weights of denominations 2, 20 and 200.

4 IRON AND STEEL WEIGHTS

4.1 Hexagonal Weights

4.1.1 Denominations

The denominations, shall be as given in 3.1.1.

4.1.2 Material

4.1.2.1 Weights of 50 kg down to and including 5 kg shall be made of cast iron only. Cast iron weights may preferably be made from material conforming to grade FG 150 of IS 210.

4.1.2.2 Weights of 2 kg down to and including 50 g shall be made either of cast iron or of forged mild steel as specified by the purchaser. Mild steel weights may preferably be made from material conforming to steel Designation Fe 310-0 of IS 1977.

4.1.3 Shapes and Dimensions

The shapes and dimensions of cast iron weights shall conform to Fig. 1 and Fig. 2 read with Tables 1 and 2 and those of mild steel shall conform to Fig. 2 read with Table 2.

4.1.4 Cast-in Handles

Handles of denominations of 50 kg down to and including 5 kg shall be provided with cast-in handles made of mild steel, which may conform to steel Designation Fe 310-0 of IS 1977.

4.1.5 Nesting of Weights

Weights of denominations of 2 kg down to and including 50 g shall nest with each other.

4.1.6 Loading Holes

Weights of denominations of 50 kg down to and including 5 kg with cast-in handles (*see* Fig. 1) shall have one rectangular loading hole on the under surface, tapering outwards along the width. While nesting, weights (*see* Fig. 2) of denominations of 2 kg down to and including 50 g shall have one round loading hole tapering outwards in the centre of the underside.

4.1.7 Permissible Errors

The errors in excess permissible for adjusted new weights shall not exceed the following limits:

<i>Denominations</i>	<i>Permissible Errors in Excess</i>
50 kg	7 500 mg
20 kg	3 000 mg
10 kg	1 500 mg
5 kg	750 mg
2 kg	300 mg
1 kg	150 mg
500 g	75 mg
200 g	30 mg
100 g	15 mg
50 g	10 mg

4.2 Brass and Bronze Weights

4.2.1 Denominations

The denominations shall be as given in 3.1.1.

4.2.2 Materials

The weights shall be made of cast brass or cast bronze or pressed or turned from brass rods. The cast brass and brass rods may preferably conform to Designation LCB 2 of IS 292 and IS 319. Cast bronze may preferably conform to IS 306.

4.2.3 Shapes and Dimensions of Weights

4.2.3.1 Weights of denominations of 10 kg down to and including 1 g shall be cylindrical in shape, with a knob. Shapes and dimensions shall conform to Fig. 3 read with Table 3 and Table 4 respectively. Bullion weights of 10 kg down to and including 200 g shall be marked on the knob with the words 'Bullion' and 'बुलियन' within a 'diamond' and weights of 100 g down to and including 1 g shall be marked on the body with only a 'diamond' as shown in Fig. 4.

4.2.3.2 Weights of denominations 1 kg down to and including 1 g shall be flat cylindrical in shape (without a knob) and shall nest with each other. Shapes and dimensions shall conform to Fig. 4 read with Table 5. Weights of 1 kg down to and including 20 g shall be marked with the words 'Bullion' and 'बुलियन' within a 'diamond' as shown in Fig. 4 and weights of 10 g and below down to and including 1 g shall be marked with only a 'diamond'.




FIG. 1 CAST IRON WEIGHT WITH CAST-IN HANDLE

Table 1 Dimensions for Cast Iron Weights with Cast-in Handle
(Clause 4.1.3, and Fig. 1)

All dimensions in millimetres.

Sl No.	Denominations kg	A	B	C	D	E	G	P	Q	R	S	d
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)
i)	50	236	253	134	170	100	27	58	48	24	102	32
ii)	20	188	200	112	113	90	21	44	38	19	66	22
iii)	10	152	161	92	88	74	18	36	30	15	54	19
iv)	5	125	132	75	65	62	15	29	25	12	40	16

NOTE — Tolerance on all dimensions shall be ± 5 percent.





FIG. 2 CAST IRON OR FORGED MILD STEEL WEIGHT

Table 2 Dimensions for Cast Iron Weight or Forged Mild Steel Weights
(Clause 4.1.3, and Fig. 2)



All dimensions in millimetres.

Sl No.	Denomina- tions	A	B	C	D	H	P	Q	R	S	T
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
i)	2 kg	94	101	78	41	10	34	30	9	18	4
ii)	1 kg	73	79	62	34	8	32	28	8	16	4
iii)	500 g	57	62	47	27	6	23	20	6	13	3
iv)	200 g	42	48	38	21	6	22	20	4	9	3
v)	100 g	33	38	31	17	5	18	16	3	7	2.5
vi)	50 g	27	31	24	12	3	16	14	3	5	2




NOTE — Tolerance on dimensions:
a) For weights above 1 kg, ± 5 percent.
b) For weights 1 kg and below, ± 10 percent.



LOADING HOLE
TYPE A



LOADING HOLE
TYPE B



MANUFACTURER'S NAME
OR TRADE MARK





FIG. 3 CYLINDRICAL, KNOB TYPE WEIGHTS

Table 3 Dimensions for Cylindrical Bullion Weights with Knob
(Clause 4.2.3.1, and Fig. 3)

All dimensions in millimetres.

Sl No.	Denominations	<i>U</i>	<i>V</i>	<i>W</i>	<i>H</i>	<i>Y</i>	<i>R</i>	<i>J</i>	<i>K</i>
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)
i)	10 kg	100	90	58		17	15	3	10
ii)	5 kg	80	72	46		13	12	2	10
iii)	2 kg	60	54	36		10	9	2	5
iv)	1 kg	48	43	27		8	7	2	5
v)	500 g	38	34	22		6	5.5	1.5	3.2
vi)	200 g	28	25	16	According to material	4.5	4	1.5	3.2
vii)	100 g	22	20	13		4	3.5	1	2
viii)	50 g	18	16	10		3	2.5	1	2
ix)	20 g	13	11.5	7.5		2	1.8	0.5	1.5
x)	10 g	10	9	6		1.6	1.5	0.5	1
xi)	5 g	8	7	4.5		1.4	1.25	0.5	1
xii)	2 g	6	5.5	3		1	0.9	0.5	1
xiii)	1 g	6	5.5	3		1	0.9	0.5	1

Without loading hole

NOTE — Tolerance on dimensions:

a) For weights above 1 kg, ± 5 percent.

b) For weights 1 kg and below, ± 10 percent.

Table 4 Cylindrical Knob Type Weights — Dimensions for Landing Hole Varieties I and II
(Clause 4.2.3.1, and Fig. 3)

All dimensions in millimetres.

Sl No.	Denominations	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>	<i>F</i>	<i>G</i>	<i>L</i>	<i>T</i>	<i>I</i>	<i>M</i>	<i>N</i>	<i>P</i>	<i>S</i>
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)
i)	20 g	3	18	5.5	2.5	6.5	1.5	1	9	M 4 \times 0.5	5	1	5	5	1
ii)	50 g	4.5	25	7.5	3.5	9	2	1	10	M 6 \times 0.5	5	1.5	7	7	1.5
iii)	100 g	4.5	30	7.5	3.5	9	2	1.5	10	M 6 \times 0.5	5	1.5	7	7	1.5
iv)	200 g	7	40	10.5	4.5	12	2.5	1.5	15	M 8 \times 1	8	2	10	10	2
v)	500 g	7	50	10.5	4.5	12	2.5	2.5	15	M 8 \times 1	8	2	10	10	2
vi)	1 kg	12	65	18.5	7	20	4	2.5	20	M 14 \times 1.5	13	3	18	18	3
vii)	2 kg	12	80	18.5	7	20	4	2.5	20	M 14 \times 1.5	13	3	18	18	3
viii)	5 kg	18	120	24.5	8	26.5	4	2.5	35	M 20 \times 1.5	18	4	24	24	3
ix)	10 kg	18	160	24.5	8	26.5	4	2.5	35	M 20 \times 1.5	18	4	24	24	3

NOTE — Tolerance on dimensions:

a) For weights above 1 kg, ± 5 percent.

b) For weights 1 kg and below, ± 10 percent.




FIG. 4 FLAT CYLINDRICAL BULLION WEIGHT

Table 5 Dimensions for Flat Cylindrical Bullion Weights
(Clause 4.2.3.2, and Fig. 4)

All dimensions in millimetres.

Sl No.	Denomina- tions	A	B	C	D	E	F	G
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	1 kg	80	61.5	20	23	4.0	12	26.6
ii)	500 g	61	48.5	16	19	2.5	10	22.5
iii)	200 g	48	37.5	14	16	2.0	7	14.8
iv)	100 g	37	28.5	12	14	2.0	6	12.7
v)	50 g	28	21.5	10	11	1.5	5	11.0
vi)	20 g	21	16.5	9	10	1.5	3	8.4
vii)	10 g	16	12.5	—	—	1.5	—	6.9
viii)	5 g	12	9.5	—	—	1.0	—	5.9
ix)	2 g	9	7.0	—	—	1.0	—	4.4
x)	1 g	6.5	—	—	—	—	—	3.6

NOTE — Tolerance on all dimensions, ± 10 percent.

4.2.4 Loading Hole

4.2.4.1 Weights of denominations 10 g to 1 g, both inclusive, shall be solid, integral weights without a loading hole.

4.2.4.2 Weights of denominations 10 kg to 20 g, both inclusive, shall be solid, integral weights without a loading hole.

4.2.4.3 The loading hole of cylindrical knob type shall be cylindrical and pass through the axis of the weight open out on the upper surface of the knob and have wider diameter at its upper end as shown in Fig. 3.

4.2.4.4 The loading hole shall be closed either by means of a threaded brass plug or a flat brass disc (*see* Fig. 3).

NOTES

- 1 The thread used shall be that commonly known as 'ISO' metric.
- 2 Threaded plug shall have a slot for adjusting it by means of a screw driver.
- 3 The flat disc shall be provided with a suitable hole in the centre to facilitate handling.

4.2.4.5 The plug or the flat disc shall be closed by means of lead pallet pressed firmly into the circular groove in the wider part of the loading hole.

4.2.4.6 Weights without a loading hole shall be adjusted by matching or grinding.

4.2.4.7 Weights with loading hole shall be adjusted with heavy metallic materials such as lead shots.

4.2.4.8 In the case of new weights about two thirds of the depth of the loading hole shall remain empty after adjustment.

4.2.5 Permissible Errors

The errors in excess permissible for adjusted new weights shall not exceed the following limits:

Denominations	Permissible Errors in Excess	
	Other than Bullion Weights mg	Bullion Weights mg
(1)	(2)	(3)
10 kg	1 500	500
5 kg	750	250
2 kg	300	100
1 kg	150	50
500 g	75	25

(1)	(2)	(3)
200 g	30	10
100 g	15	5
50 g	10	3
20 g	8	2.5
10 g	6	2
5 g	5	1.5
2 g	4	1.2
1 g	3	1

4.3 Sheet Metal Weights

4.3.1 Denominations

Denominations, shall be as given in 3.1.2.

4.3.2 Materials

Sheet metal weights shall be made of stainless steel, aluminium, brass or nickel-silver sheets. The aluminium and brass weights may preferably conform to Designation 64430 Condition O of IS 737 and Alloy Designation CuZn40 of IS 410 respectively.

4.3.2.1 Nickel silver steel

Nickel silver sheet should preferably have the following composition:

Constituent	Percent by Weight
Copper	63.0 to 66.5
Nickel	17.5 to 19.5
Zinc	Remainder

4.3.2.2 Stainless steel sheet

Stainless steel sheet may preferably conform to Designation X 07 Cr18Ni9 of IS 1570 (Part 5).

4.3.3 Shapes and Dimensions

4.3.3.1 Other than bullion weights

After bending along one of the sides (*see* Fig. 5) the weights shall have the dimensions given in Table 6 and the following shapes:

Denomination mg	Shape
500, 50, 5	Hexagon
200, 20, 2	Square
100, 10, 1	Triangle




FIG. 5 SHEET METAL WEIGHTS

Table 6 Dimensions for Sheet Metal Weights
(Clause 4.3.3.1, and Fig. 5)

All dimensions in millimetres.

Sl No.	Denomination	A_1	A_2	A_3	B	H
(1)	(2)	(3)	(4)	(5)	(6)	(7)
i)	500 mg	14.0	—	—	2.0	3.0
ii)	200 mg	—	12.0	—	2.0	3.0
iii)	100 mg	—	—	12.0	2.0	2.5
iv)	50 mg	8.0	—	—	1.5	2.5
v)	20 mg	—	7.0	—	1.5	2.5
vi)	10 mg	—	—	7.0	1.5	2.5
vii)	5 mg	4.5	—	—	1.0	2.0
viii)	2 mg	—	4.0	—	1.0	2.0
ix)	1 mg	—	—	4.0	1.0	2.0

NOTE — Tolerance on all dimensions, ± 10 percent.

4.3.3.2 Bullion weights

When intended for use in the bullion trade sheet metal

weights shall, after bending, have circular shape; their diameters shall be as given in Fig. 6 read with Table 7.




FIG. 6 SHEET METAL BULLION WEIGHT

Table 7 Dimensions for Sheet Metal Weights (Bullion)
(Clause 4.3.3.2, and Fig.6)

All dimensions in millimetres.

SI No.	Denominations mg	D	C	H
(1)	(2)	(3)	(4)	(5)
i)	500	15	2.0	3.0
ii)	200	13	2.0	3.0
iii)	100	11	2.0	2.5
iv)	50	9	1.5	2.5
v)	20	8	1.5	2.5
vi)	10	7	1.5	2.5
vii)	5	6	1.0	2.0
viii)	2	5	1.0	2.0
ix)	1	4	1.0	2.0

NOTE — Tolerance on all dimensions, ±10 percent.

4.3.4 Permissible Errors

The errors in excess permissible for new weights shall not exceed the following limits:

Denomination	Permissible Errors in Excess	
	Other than Bullion Weights mg	Bullion Weights mg
mg		
500	2.5	0.8
200	2.0	0.6
100	1.5	0.5
50	1.2	0.4
20	1.0	0.3
10	0.8	0.25
5	0.6	0.20
2	0.6	0.20
1	0.6	0.20

5 MANUFACTURE AND FINISH

5.1 General

When the weights are cast, the castings shall be reasonably smooth and free from dross, pits, blowholes and other defects. When the weights are made by machining or forging, the surface shall be reasonably smooth. Sheet metal weights shall be clearly sheared and shall be free from burrs. Cast iron and forged weights shall be coated with a thin film of suitable black paint or varnish.

5.2 The raised marking on weights shall be clean and legible. The stamped markings on sheet metal weights shall be legible and deep enough to ensure indelibility over a long period, but not so deep as to crack the sheet (*see also 6*).

5.3 When lead is used in adjusting weights, it shall be so fitted as to ensure that it does not dislodge itself under normal conditions of use (*see also 6*).

5.4 The steel handles of cast iron weights shall be rigidly fixed.

6 MARKING

6.1 Every weight except weights of 20 g and lower

denominations shall have the manufacturer's name and/or trade-mark indelibly cast or stamped on it.

6.2 The denominations shall be indicated in an indelible manner, with the abbreviations 'kg' and 'किलो' to indicate kilogram, 'g' and 'ग्राम' to indicate gram, and 'mg' and 'मिग्राम' to indicate milligram. The size of numerals and letters (letters need not be stamped on weights 50 mg and below and on bullion weights with knobs of denominations 5 g and below) indicating denominations of weights shall be at least twice the size of letters indicating the manufacturer's name or trade-mark. The numerals used in the denominations shall be indicated in the international form of Indian numerals.

6.3 The smallest weight which can be stamped fully are the 10 g cylindrical knob type weights and 2 g flat cylindrical bullion weights. All weights from 10 g cylindrical knob type and 2 g flat cylindrical and above, shall be stamped with all 3 stamps. Weights of 20 mg shall be stamped with one stamp only, that is, the date stamp. Weights of 10 mg and below shall not be stamped at all. If they are contained in a box, the box shall be stamped and certified. If there is no box, the weights shall be authenticated by a certificate of verification.

NOTE — Abbreviation 'किलो' or 'किग्रा' may be indicated in the regional script.

6.4 BIS Certification Marking

The product may also be marked with the Standard Mark. If it is not possible to put the Standard Mark on the product then it may be marked on packing or packing box in which the product is packed.

6.4.1 The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

7 ADJUSTMENTS

The weights provided with loading holes shall be adjusted by pouring the required weighed quantity of molten lead into the loading hole and pressing the lead firmly. The approximate distance of the lead, from the surface shall be not less than 20 percent of the minimum thickness of the weight when new.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc : No. BP 26 (0218).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002
Telephones : 2323 0131, 2323 33 75, 2323 9402

Telegrams : Manaksanstha
(Common to all offices)

Regional Offices :

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110 002	{ 2323 7617 2323 3841
Eastern : 1/14 C.I.T. Scheme VII M, V. I. P. Road, Kankurgachi KOLKATA 700 054	{ 2337 8499, 2337 8561 2337 8626, 2337 9120
Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022	{ 60 3843 60 9285
Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600 113	{ 2254 1216, 2254 1442 2254 2519, 2254 2315
Western : Manakalaya, E9 MIDC, Marol, Andheri (East) MUMBAI 400 093	{ 2832 9295, 2832 7858 2832 7891, 2832 7892
Branches : AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM.	